



XNT Soldering Tip Family

**Compatibile con gli stili
saldanti:
WXP 65
WXP 90
WP 65
WTP 90**

- + Most difficult, high mass soldering jobs
- + Maximum power and response for top performance
- + Optimal balance between power, control and running costs with wide range of tips
- + Highest quality soldering standard for widest range of applications



	Article	a / b (mm) / (inch)	Article	a / b (mm) / (inch)	Article	a / b (mm) / (inch)	
Chisel 	XNT A T0054485199 BESTSELLER	1.6 mm / 0.4 mm 0.063 inch / 0.016 inch	XNT CS T0054487099	3.2 mm / 0.8 mm 0.126 inch / 0.315 inch	XNT MX T0054488399	3.2 mm / 0.8 mm 0.126 inch / 0.315 inch	
	XNT AX T0054486499	1.6 mm / 0.8 mm 0.063 inch / 0.315 inch	XNT D T0054485399	4 mm / 0.8 mm 0.157 inch / 0.315 inch	XNT 6 T0054485699	1.6 mm / 0.4 mm 0.063 inch / 0.016 inch	
	XNT B T0054485799 BESTSELLER	2.4 mm / 0.8 mm 0.094 inch / 0.315 inch	XNT H T0054485999 BESTSELLER	0.8 mm / 0.4 mm 0.031 inch / 0.016 inch	XNT 1SC T0054486299 BESTSELLER	0.4 mm / 0.15 mm 0.016 inch / 0.006 inch	
	XNT BX T0054488299	2.4 mm / 0.8 mm 0.094 inch / 0.315 inch	XNT K T0054486099	1.2 mm / 0.4 mm 0.047 inch / 0.016 inch	XNT 1SCNW T0054488199	0.3 mm / 0.1 mm 0.012 inch / 0.004 inch	
	XNT C T0054485899 only US	3.2 mm / 0.8 mm 0.126 inch / 0.315 inch	XNT L T0054486699	3.2 mm / 0.8 mm 0.126 inch / 0.315 inch	XNT 4X 45° T0054487499	1.2 mm / 0.4 mm 0.047 inch / 0.016 inch	
Round 	XNT 1L T0054487199	0.2 mm 0.008 inch	XNT 4 T0054485599	1.2 mm 0.047 inch	High mass soldering jobs 	Power Response 	Heat up time °C 350 300 200 100 0 5 Sec.* *from 50°C to 350°C / 120°F to 620°F
	XNT 1LX T0054487299	0.2 mm 0.008 inch	XNT AA 45° T0054488499	1.6 mm 0.063 inch			
	XNT 1S T0054485299	0.2 mm 0.008 inch	XNT BB 45° T0054488599	2.4 mm 0.094 inch			
	XNT 1SLX 45° T0054487599	0.4 mm 0.016 inch	XNT CC 45° T0054488699	3.2 mm 0.126 inch			
	XNT 1X T0054486599	0.4 mm 0.016 inch	XNT F 45° T0054488799	1.2 mm 0.047 inch			
	XNT AS T0054486999 only US	1.6 mm 0.063 inch					
Conical 	XNT 1 T0054485099 BESTSELLER	0.5 mm 0.02 inch	Measuring tip Measuring tip T0054486199N 				
	XNT S T0054486899	0.4 mm 0.016 inch					
Gullwing 	XNT GW1 T0054485499	1.6 mm 0.063 inch					
	XNT GW2 short T0054488099	1.0 mm 0.039 inch					
Knife 	XNT KN T0054486399	2.0 mm 0.079 inch					

Power Response **Component size** XS TO M

Heat up time 5 Sec.*

*from 50°C to 350°C / 120°F to 620°F

High mass soldering jobs

Weller®

weller-tools.com/toolselector/en
weller-tools.com/toolselector/us