


## Condensatori elettrolitici

### LOW ESR SERIE TS13CA 47UF 35V Ø6.3X5.8MM IN REEL

COND EL M 47uF 35V TS13CA smd 6.3x5.8

Codice Adimpex: **C2204735SU**

P/N: **TS13CA1V470MFT000R**



\*1 Voltage mark for 35V is [35V] or [35]  
 For Data code and series type:  
 1st digit for series  
 2nd digit for Capacitor type  
 3rd digit for Voltage  
 4th digit for Capacitance  
 5th digit for Tolerance  
 6th digit for Temperature  
 7th digit for RoHS  
 8th digit for Manufacturer

\*2 Markings: SVA, SA, FZ

| Code | Value | Series | Capacitance | Voltage | Temperature | RoHS | Manufacturer |
|------|-------|--------|-------------|---------|-------------|------|--------------|
| 1    | 1.0   | 1.0    | 1.0         | 1.0     | 1.0         | 1.0  | 1.0          |
| 2    | 2.2   | 2.2    | 2.2         | 2.2     | 2.2         | 2.2  | 2.2          |
| 3    | 3.3   | 3.3    | 3.3         | 3.3     | 3.3         | 3.3  | 3.3          |
| 4    | 4.7   | 4.7    | 4.7         | 4.7     | 4.7         | 4.7  | 4.7          |
| 5    | 5.6   | 5.6    | 5.6         | 5.6     | 5.6         | 5.6  | 5.6          |
| 6    | 6.8   | 6.8    | 6.8         | 6.8     | 6.8         | 6.8  | 6.8          |
| 7    | 8.2   | 8.2    | 8.2         | 8.2     | 8.2         | 8.2  | 8.2          |
| 8    | 10    | 10     | 10          | 10      | 10          | 10   | 10           |
| 9    | 12    | 12     | 12          | 12      | 12          | 12   | 12           |

## Caratteristiche Tecniche:

|                               |                       |
|-------------------------------|-----------------------|
| Temperatura e cicli vita:     | 105°C - 2000/5000Hrs  |
| Tensione:                     | 35 V                  |
| Capacità (µF):                | 47                    |
| Dimensione elettrolitici SMD: | 6.3x5.8               |
| Tipologia:                    | Low ESR/Low impedance |
| Montaggio:                    | SMD                   |