

Condensatori ceramici e multistrato

CERAMICO MULTISTRATO PTH 50V 100KPF Y5V SERIE TS17 IN BUSTA

COND Y5V M50 100Kpf p2.54mu IK t.3mm BULK*

Codice Adimpex: **COH21414-R**

P/N: **TS17R p.2,54 BULK H=3mm**



Size Codes, Capacitance and Voltage										
Size code	Shape	Dimensions (mm)				Tmax	Voltage	Capacitance (pF)		
		W (0.5)	Length	Width	Thickness			CSG(NPVS)	SW	Y5V(Z5U)
6805	b	2.54	4.2	3.8	3.0	25V	OMS-103	103-105	103-475	103-475
	C1	5.08	4.2	3.8	3.0	50V	OMS-103	103-474	103-474	103-105
	C3	5.08	4.2	3.8	3.0	100V	OMS-103	103-104	103-104	103-104
1206	a	2.54	5.0	4.5	3.5	25V	OMS-104	103-225	103-106	103-106
	b	3.5	5.0	4.5	3.5	50V	OMS-473	103-225	103-106	103-106
	C1	5.08	5.0	4.5	3.5	100V	OMS-473	103-105	103-155	103-155
1210	a	2.54	5.0	4.5	3.5	25V	OMS-104	103-106	103-106	103-106
	b	3.5	5.0	4.5	3.5	50V	OMS-473	103-475	103-106	103-106
	C1	5.08	5.0	4.5	3.5	100V	OMS-473	103-105	103-155	103-155
1812	b	5.08	7.0	6.0	4.0	25V	OMS-104	103-106	103-106	103-106
	C1	5.08	7.0	6.0	4.0	50V	OMS-104	103-106	103-106	103-106
	C3	5.08	7.0	6.0	4.0	100V	OMS-473	103-105	103-155	103-155
2225	b	5.5	10	9	4.5	25V	OMS-104	103-106	103-106	103-106
	C1	5.5	10	9	4.5	50V	OMS-104	103-106	103-106	103-106
	C3	5.5	10	9	4.5	100V	OMS-473	103-105	103-155	103-155
3035	b	7.5	12	10	4.5	25V	OMS-104	103-106	103-106	103-106
	C1	7.5	12	10	4.5	50V	OMS-104	103-106	103-106	103-106
	C3	7.5	12	10	4.5	100V	OMS-473	103-105	103-155	103-155

Caratteristiche Tecniche:

Tolleranza:	±20% (Y5V)
Capacità (F):	100KpF
Pitch (mm):	2,54
Tensione:	50 V
Tipologia:	Multistrato PTH