

Condensatori ceramici e multistrato

CERAMICO MULTISTRATO PTH 100V 100KPF Y5V SERIE TS17 IN REEL (KINKED PIN)

COND Y5V M100 100Kp IK p5ms-NS

Codice Adimpex: **COH79410-R**

P/N: **TS170R2A104MSAFB0R kinked**



◆ Size Code, Capacitance and Voltage										
Size	code	cap	P (kV)	Len	Wmax	Temp	Subst	COG(NP)	X7R	Y5V(25)
	b	254	4.2	3.8	3.0	25V	ORS-103	101-102	101-475	
	C1	508	4.2	3.8	3.0	50V	ORS-103	101-476	101-105	
	C3	508	4.2	5.0	3.0	100V	ORS-103	101-106	101-104	
	a	254	3.0	4.5	3.5	25V	ORS-104	101-225	101-106	
	b	3.5	3.0	4.5	3.5	50V	ORS-473	101-225	101-106	
	C1	508	3.0	4.5	3.5	100V	ORS-473	101-105	101-105	
	a	254	3.0	4.5	3.5	25V	ORS-104	101-106	101-106	
	b	3.5	3.0	4.5	3.5	50V	ORS-473	101-475	101-106	
	C1	508	3.0	4.5	3.5	100V	ORS-473	101-105	101-105	
	b	508	7.0	6.0	4.0	25V	ORS-104	101-106	101-106	
						50V	ORS-104	101-106	101-106	
						100V	ORS-473	101-105	101-105	
	b	5.5	10	9	4.5	25V	ORS-104	101-106	101-106	
						50V	ORS-104	101-106	101-106	
						100V	ORS-473	101-105	101-105	
	b	7.5	12	10	4.5	25V	ORS-104	101-106	101-106	
						50V	ORS-104	101-106	101-106	
						100V	ORS-473	101-105	101-105	

Caratteristiche Tecniche:

Tolleranza:	±20% (Y5V)
Tensione:	100 V
Capacità (F):	100KpF
Pitch (mm):	5
Tipologia:	Multistrato PTH