


Plug e jack DC

PLUG DC FEMMINA Ø2,1MM 90°

D5.5/2.1/9.5 DP-RA-L 90° TW

Codice Adimpex: **GLP00981-R**

P/N: **DP-RA-L (2.1-5.5-9.5 RIGHT ANGLE)**



DP-RA	X	Y	Z
A	0.7	2.5	10
B	1.0	3.5	10
C	1.0	5.5	9.5
D	1.0	2	10
E	1.3	3.5	9.5
F	1.3	5.5	9.5
G	1.3	3.5	14
H	1.7	4	9.5
J	1.7	4.75	9.5
K	1.7	5	10
L	2.1	5.5	9.5
M	2.1	5.5	14
N	2.5	5.5	9
O	2.5	5.5	9.5
P	2.5	5.5	14
S	3.1	5.5	9.5
T	3.1	6.3	10

Specification
 1. Rating : 247WDC
 2. Withstanding voltage
 AC 500V - 60Hz for 1 minute
 3. Insulation resistance (1000V)
 500M ohm/min at 500VDC
 4. Contact resistance (100V)
 5. Insulation & Extrusion force
 6.2 to 12 kg
 After life test : 0.2 to 0.5 kg
 7. Life test (20-30 cycles/min)
 5,000 cycles withstanding
 DC PLUG
 (RIGHT ANGLE TYPE)

Caratteristiche Tecniche:

Orientamento:	90 gradi
Tipologia:	Femmina
Configurazione:	Ø2,1 L 9,5